
# welding sleeves and sealing plugs

## features

- dead space- and elastomer free process adaption for temperature sensor WTR 150, WTR 350, WTR 450, WTR 550, WTR 390, WTR 395, WTR 490, WTR 495, level switch NGS150, NGS 250, level rod probes NST150, NST250, ...
- hygienical compatible mounting in cases and pipelines in all areas of the food
- and pharma industry
- EHEDG and FDA-conform
- marking of PG-position by lasermarking at the sleeve
- material 1.4404 (316L), other materials on request
- on request deliverable with material certificates

### principle of function

 the taper at screw neck of sensors will be pushed to the seal face of welded sleeve while screwing into the thread. Due to this a metallic seal without further elastomere seals will be obtained.



without connection (open)

### with connection (closed)

### assembly advice

Important: use only welded sleeves of company promesstec, to reach a secure and optimal measuring point. Pay attention to the max. acceptable clamping torque at assembly.

### welded sleeves and sealing plugs G1/2" sealing system

| G1/2"       |                            |   | Cod  |                                |   |
|-------------|----------------------------|---|--|--------------------------------|---|
|             | ø30<br>G1/2"<br>ø19<br>ø35 | ©10<br>G12<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0 | Ø29<br>G1/2"<br>Ø<br>Ø<br>Ø<br>Ø<br>Ø<br>Ø<br>Ø<br>Ø | 5 W 22<br>5 X<br>1<br>0<br>018 |   |
| designation | modular welded<br>sleeve   | cylindric welded<br>sleeve without<br>flange                                | cylindric welded sleeve with neck                    | sealing plug                   | welded helping<br>plug of brass (use<br>only for weld in) |
| type        | KEM 150                    | ZEM 150   | ZEM 151  | VSS 150                        | ESH 150   |



# welding sleeves and sealing plugs

# welded sleeves and sealing plugs G1" sealing system

| G1"         |                                      |                                      |   |
|-------------|--------------------------------------|--------------------------------------|---|
|             |                                      | SW 36                                |   |
| designation | cylindric welded sleeve without neck | sealing plug made of stainless steel | welded helping plug of brass (use only for weld in) |
| type        | ZEM 950                              | VSS 950                              | ESH 950   |

# welded sleeves and sealing plugs M12 sealing system

| M12         |                                    |  |  |              |
|-------------|------------------------------------|--|--|--------------|
|             | M12x1.5                            | 017<br>HM12x154                        | M12x1,5<br>1<br>2<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1 |              |
| designation | weld-in ball sleeve without flange | cylindrical weld-in sleeve with flange | cylindrical weld-in sleeve without flange  | sealing plug |
| type        | KEM 050                            | ZEM 050                                | ZEM 051  | VSS 050      |

version 2.1.1 page 2



# welding sleeves and sealing plugs

# adapter for transitions and welded sleeves of other producers adapter sleeve Image: sleeve <t